# All models with Near Field Communication Technology Bluetooth available as an option

## Digital Hand-Held "Pocket" Refractometer PAL Special Scales

Cat.No.	Model	Scale	Cat.No.	Model	Scale	Cat.No.	Model	Scale
ood, Co	onfectionery, l	Food Ingredients	4404	PAL-04S	Sodium chloride (S.G.)	4491	PAL-91S	Ethylene glycol Freezing point of
422	PAL-22S	Honey moisture	4405	PAL-05S	Sodium chloride (Baume)			Ethylene glycol (°C)
508	PAL-Pâtissier	Brix / Baume (Dual scale)	4406	PAL-06S	Seawater (Concentration)	4492	PAL-92S	Ethylene glycol Freezing point of Ethylene glycol (°F)
807	PAL-MILK	Non-fat milk solids	4407	PAL-07S	Seawater (S.G.)	Rofracti	ve Index • Brix	
427	PAL-27S	Soymilk	4408	PAL-08S	Seawater (Baume)	3852	PAL-BX/RI	Brix / Refractive Index
443	PAL-43S	Bittern (Magnesium chloride)	Moistur			3850	PAL-RI	Refractive Index
496	PAL-96S	Chinese noodle soup / Baume of	4573	PAL-Moisture	Moisture	3840	PAL-α	Brix
400	DAI OOC	Kansui (Dual scale)	4574	PAL-Dried	Moisture	3842	PAL-LOOP	Brix
498	PAL-98S	Condiment	4575	Fruit Moisture			al products	DIA
439	PAL-39S	Hydrogen peroxide	4575	PAL-Dates Moisture	Moisture	4421	PAL-21S	Dextrin
129	PAL-29S	Citric acid Acetic acid	Clinical			4438	PAL-38S	Dimethylformamide
430	PAL-30S PAL-32S		4442	PAL-42S	Cesium chloride	4440	PAL-40S	Sodium hydroxide
432 440		Phosphoric acid Sodium hydroxide	4453	PAL-53S	Copper sulfate (Concentration)	4423	PAL-23S	Glycerin (Low concentration)
	PAL-40S PAL-64S	Sodium hydroxide Sodium bicarbonate	4454	PAL-54S	Copper sulfate (S.G.)	4424	PAL-24S	Glycerin (High concentration)
		Sodium tartrate	4410	PAL-10S	Urine (S.G.)	4430	PAL-30S	Acetic acid
	PAL-65S		4401	PAL-11S	Serum protein	4431	PAL-31S	Formic acid
470	PAL-70S	Potassium phosphate	4529		NEW Dog Urine (S.G.) / Cat Urine (S.G.)	4432	PAL-32S	Phosphoric acid
523 532	PAL-COFFEE		4510	PAL-DOGGCAT	Dog Urine (S.G.)	4444	PAL-44S	Lithium chloride
032	PAL-COFFEE (TDS)	103	4511	PAL-CAT	Cat Urine (S.G.)	4445	PAL-45S	Barium chloride
533		Brix / TDS (Dual scale)	4512		Rabbit Urine (S.G.)	4446	PAL-46S	Cobalt chloride
333	(BX/TDS)	blix / 103 (bual scale)	Colostri		habbit office (3.d.)	4447	PAL-47S	Ferric chloride
535	PAL-Tea	Tea	3805	PAL-Colostrum	Colostrum	4448	PAL-48S	Strontium chloride
ruit and	d Vegetable G	irowers	Alcohol		Colosti um	4449	PAL-49S	Potassium chloride
847	PAL-ORANGE		4433	PAL-33S	Ethyl alcohol (mL/100mL)	4450	PAL-50S	Potassium bromide
848	PAL-TOMATO	Brix	4434	PAL-34S	Ethyl alcohol (g/100g)	4451	PAL-51S	Sodium bromide
8849	PAL-MAPLE	Brix	4436	PAL-345	Methyl alcohol	4452	PAL-52S	Potassium iodide
ugar			4437	PAL-303	Isopropyl alcohol (g/100g)	4453	PAL-53S	Copper sulfate (Concentration)
	PAL-12S	Dextran	4530	PAL-373	Isopropyl alcohol (mL/100mL)	4454	PAL-533	Copper sulfate (S.G.)
	PAL-14S	Fructose	4485	PAL-85S	Polyvinyl alcohol	4455	PAL-55S	Magnesium sulfate
	PAL-15S	Glucose		ceutical reage		4456	PAL-56S	Potassium sulfate
	PAL-16S	High Fructose Corn syrup (HFCS-42)	4412	PAL-12S	Dextran	4457	PAL-505	Nickel sulfate
417	PAL-17S	High Fructose Corn syrup (HFCS-55)	4413	PAL-123	Creatine	4458	PAL-575	Sodium sulfate
1418	PAL-18S	Inverted suger	4413	PAL-133 PAL-23S	Glycerin (Low concentration)	4459	PAL-505 PAL-59S	Zinc sulfate
	PAL-19S	Lactose	4424	PAL-233	Glycerin (High concentration)	4460	PAL-593	Silver nitrate
	PAL-20S	Maltose		PAL-243 PAL-25S	Inulin		PAL-603 PAL-61S	Sodium nitrate
Vine, Br			4425			4461		
479	PAL-79S	T.A. 1990	4426	PAL-26S	Mannitol Formic acid	4462	PAL-62S PAL-63S	Potassium carbonate Sodium carbonate
	PAL-80S	T.A. 1971	4431 4432	PAL-31S PAL-32S	Formic acid	4463 4464	PAL-633 PAL-64S	Sodium bicarbonate
1483	PAL-83S	KMW (or Babo)			Phosphoric acid			Potassium chromate
	PAL-84S	Baume	4451	PAL-51S	Sodium bromide	4467	PAL-67S	
	PAL-86S	Oe (Ger) / Brix (Dual scale)	4455	PAL-55S	Magnesium sulfate	4468	PAL-68S	Potassium dichromate Sodium thiosulfate
	PAL-87S	Oe (Oechsle) / Brix (Dual scale)	4464	PAL-64S	Sodium bicarbonate	4469	PAL-69S	
		Ethyl alcohol	4465	PAL-65S	Sodium tartrate	4470	PAL-70S	Potassium phosphate
1541	PAL-Vodka	Ethyl alcohol	4466	PAL-66S	Potassium oxalate	4471	PAL-71S	Sodium molybdate
542	PAL-Tequila	Ethyl alcohol	4468	PAL-68S	Potassium dichromate	4472	PAL-72S	Sodium tungstate
1543		Ethyl alcohol	4470	PAL-70S	Potassium phosphate	Metal w		6
1544		Ethyl alcohol	4472	PAL-72S	Sodium tungstate	4502	PAL-102S	Cutting oil
544	PAL-Gin PAL-Rum	Ethyl alcohol			, Heat Transfer, Industrial	4537	PAL-AntiRust	
545 546		Ethyl alcohol	4518	PAL-Urea	Urea	4536	PAL-Cleaner	
	PAL-Brandy	•	4403	PAL-03S	Snow-melting agent (Sodium chloride)	4547	PAL-NMP	NEW N-methyl-2-pyrrolidone
1590	PAL-Plato	Plato (Sweet wort)	4441	PAL-41S	Snow-melting agent (Calcium chloride)	4558		NEW Hydrocarbon cleaner
	Seawater	Codium ablavida (c/100c)	4443	PAL-43S	Snow-melting agent (Magnesium chloride)	Call C	Cleaner	contamination
1403 1393	PAL-03S PAL-03CS	Sodium chloride (g/100g) Sodium chloride (g/100g) / Freezing	4488	PAL-88S	Propylene glycol Freezing point of Propylene glycol (°C)	<b>Soil, Civ</b> 4571	il engineering PAL-Soil	Gravimetric / Volumetric Soil
		point of Sodium chloride (°C) (Dual scale) Sodium chloride (q/100mL)	4489	PAL-89S	Propylene glycol Freezing point of Propylene glycol (°F)			moisture (Dual scale)

All ATAGO products are designed and manufactured in Japan.



2-6-3 Shiba-koen, Minato-ku, Tokyo 105-0011, Japan TEL: 81-3-3431-1943 FAX: 81-3-3431-1945





http://www.atago.net/ overseas@atago.net ATAGO U.S.A., Inc. TEL: 1-425-637-2107 ATAGO INDIA Instruments Pvt. Ltd. ATAGO THAILAND Co.,Ltd, PATAGO BRASIL Ltda. ATAGO ITALIA s.r.l. ATAGO CHINA Guangzhou Co.,Ltd. ATAGO RUSSIA Ltd.

ATAGO KAZAKHSTAN Ltd. TEL: 7-727-257-08-95

\* Specifications and appearance are subject to change without notice.

TEL: 55 16 3913-8400 TEL: 7-812-777-96-96

Copyright © 2019 ATAGO CO., LTD. All rights reserved. ENV.17 19081500PP Printed in Japan

"Pocket" Refractometers

# \_ series







Brix 0.0 to 53.0%

Brix 0.0 to 93.0%

PAL-S Cat.No.3860 Mode STM Brix 0.0 to 93.0% Technology Model

PAL-91S

Cat.No.4491 Ethylene glycol 0.0 to 90.0% (V/V)

**PAL-398** 

Hydrogen peroxide 0.0 to 50.0%

























## The Next Generation of Digital Refractometers





- Extremely water resistant (IP65)
- Can be washed under running water
- Will float if accidentally dropped in water





- Ergonomically designed for one-handed operation
- The innovative design makes it easy to pour out and remove a sample, but difficult to spill the sample.



Automatic Temperature Compensation (ATC)



• Mode  $S^{\text{\tiny{TM}}}$ : Mode  $S^{\text{\tiny{TM}}}$  improves repeatability of samples that cause inconsistent readings.



 Mode H<sup>™</sup>: Mode H<sup>™</sup> enables to measure the sample at high temperature in 2 seconds.



• When intense light penetrates the prism of a digital refractometer, the light waves interfere with the sensor, which may lead to inaccurate measurements. To ensure accurate measurement results, the PAL is programmed with the ELI function which displays the [nnn] warning message when intense direct light is detected. Forming a habit of shading the sample stage with your hand and re-pressing the START key (when the warning message from the ELI function is displayed) will ensure accurate measurement results each time.



- Measurement history (up to 100 items) can be read by touching a contactless IC card reader / writer connected to an Android smartphone or a personal computer.
- \* The N-Mark is a trademark or registered trademark of NFC Forum, Inc. in the United States and in other countries.



## Low to medium PAL-1

Cat.No.3810

PAL- 3 Cat.No.3830 Powered by Mode S™ PAL-S S Mode

Cat.No.3860

MAGIC<sup>TM</sup>

Standard accessory

Powered by Mode H™ PAL-H

Cat.No.3870

Ethylene glycol (V/V) PAL-91S

Cat.No.4491

PAL-39S

Cat.No.4439

## **Specifications**

	PAL-1 Cat.No.3810	PAL-3 Cat.No.3830	PAL-S Cat.No.3860	PAL-H Cat.No.3870	PAL-91S Cat.No.4491	PAL-39S Cat.No.4439	
Measurement range	Brix 0.0 to 53.0%		Brix 0.0 to 93.0%		E.G : 0.0 to 90.0 % (V/V) Freezing point : 0 to -50℃	Hydrogen peroxide 0.0 to 50.0%	
Resolution		Brix 0.1%		Brix 0.5%	E.G: 0.2 %(V/V) Freezing point: 1℃	Hydrogen peroxide 0.2%	
Measurement accuracy	Brix ±0.2%	Brix ±0.1%	Brix ±0.2%	Brix ±0.5%	E.G: ±0.4 % (Concentration of about 15%) Freezing point: ±1°C	Hydrogen peroxide ±0.6%	
Measurement temperature	10 to 100°C (ATC) (Hot samples over 100°C can be measured under specified conditions.  Please contact ATAGO for further details.)						
Ambient temperature	10 to 40°C					10 to 35℃	
Power supply	2×AAA Batteries						
International protection class	IP65 Water resistant						
Dimensions and weight	5.5×3.1×10.9cm, 100g						

## **Application examples**



## **PAL** commitment

## A new ergonomic design for comfort and ease of use!

In pursuit of an "easy to use", "easy to operate" and ergonomic architecture of new instruments, ATAGO has achieved a "palmfitting" masterpiece as well as unit that is high in hygienic properties. By reducing the number of unnecessary assembly parts, we have reduced the risks of a germ reproductive environment. Through our efforts to produce a hygienic instrument to be used in any industry, these units are designed to be completely washable. The new PAL series has been approved by the HACCP, and are equipped with the new ELI feature, which ensures accurate measurements - even outdoors Requests from our customers worldwide are reflected in the development of the new PAL units.

#### Sample Stage

The SUS sample stage allows for the sample temperature to conform quickly and evenly to the prism temperature for accurate measurements.

#### START Key

Conveniently located for single hand operation.

#### **NEW NFC**

PAL series comes with Data Function with NFC technology.



## Actua Size

(ATAGE

(ZERO)

EFRACTOMETER PAL-

## Made of highly durable optical glass to prevent scratching.

## Liquid Crystal Display (LCD)

Digital measurement values are large and easy to read. Displays battery indicator and temperature.

## **ZERO Key**

For Zero Setting, place water on the prism and press.

#### **Strap Holder**

Suitable for wrist straps or lanyards.



Apply 2-3 drops on the prism



Press the START key.



Measurement value and prism 3 Measurement value and prism temperature are displayed in 3 seconds!

## **Optional**

Part No.	Part Name.
RE-110010	Sucrose Solutions (for Brix confirmation) 10% (±0.03%)
RE-110020	Sucrose Solutions (for Brix confirmation) 20% (±0.03%)
RE-110030	Sucrose Solutions (for Brix confirmation) 30% (±0.03%)
RE-110040	Sucrose Solutions (for Brix confirmation)40% (±0.04%)
RE-110050	Sucrose Solutions (for Brix confirmation)50% (±0.05%)
RE-110060	Sucrose Solutions (for Brix confirmation)60% (±0.05%)
RE-39409	PAL-CASE
RE-39410	PAL-STRAP
RE-39446	MAGIC™
RE-39412	Small Volume Sample Adapter for PAL
RE-39413	PAL Silicone Cover







#### **◀** Sucrose Solutions tom concentrations are available on request. Accuracy and prices will

Warranty period for these solutions is 6



#### ■ MAGIC<sup>TM</sup> This adaptor is used for a hot sample to cool it down quickly or to minir









#### Systems, ATAGO can calibrate and certify your Digital Hand-Held "Pocket" Refractometer The following documents will be issued Distilled Water Saccharo (for a service 1st 3rd

Certification

Calibration Certificate

free):

In accordance with ISO

Quality Management

- Traceability System Diagram
- Traceability Certificate